

## PRODUCT INFORMATION



### CHOICE

Even 36 models with different heating power (9, 11, 14, 16, 19 and 25 kW), glazing (straight or corner) and the method of opening the door (traditional or guillotine).

### PERSONALIZATION

The possibility of individual glazing type: printed Decor, bent glass or double glazing.

### QUALITY

Fireplace inserts are made of high-quality P265GH boiler steel, which is resistant to continuous operation at higher temperature. A well reinforced door profile is used.

### REPEATABILITY

Production process use modern machinery park: welding robots, press brakes, laser cutters.

### ECOLOGY

Comply with strict emission standards and the ECODESIGN, thanks to the use of an after-burning system and high efficiency.

### SECURITY

An innovative ventilated handle protects against scalding. Suitable for homes with recuperation.

### EASY-TO-USE

The built-in intake with the throttle enables smooth integrated regulation of the amount of air supplied.

### CLEANLINESS

The air curtain provides the effect of „clean glass” and easy cleaning of the insert is possible thanks to the cast iron grate with a removable container for ash.

|  |              |
|--|--------------|
| Nominal power [kW]   | 14,0         |
| Heating load range [kW]                                    | 7-18         |
| Thermal efficiency [%]                                     | 83           |
| CO emission (by13% O <sub>2</sub> ) [g/m <sup>3</sup> ]    | 0,845        |
| Dust emission [g/m <sup>3</sup> ]                          | 0,032        |
| Average fuel consumption [kg/h]                            | 4            |
| Recommended active area of outlet grids [cm <sup>2</sup> ] | 980-1120     |
| Recommended active area of inlet grids [cm <sup>2</sup> ]  | 560-9100     |
| Dimensions of the glass [mm]                               | 680x430x375  |
| External dimensions [mm]                                   | 769x1065x510 |
| Max. log length [mm]                                       | 350          |
| Diameter of the flue [mm]                                  | 200          |
| Inlet diameter [mm]  | 125          |
| Weight [kg]  | 153          |
| Efficiency coefficient                                     | 111,4        |
| Energy class   | A+           |

### OTHER EQUIPMENT:

Ceramic deflector, heat pipes, steel flue, adjustable feet (+4 cm), heat radiators.

### ADDITIONAL OPTIONS:

Masking frames 3/4 and 4/4, additional legs (+10 cm), glass DEKOR, bent glass, double glazing.

